TECHNICAL SPECIFICATIONS

MODEL H100LSROUV50/100 Water Dispenser with Inbuilt RO/UV Purifier System

Storage: 100 Litres | Inbuilt RO: 50 Litres/Hr or 100 Litres/Hr

Model	**H100LSROUV50/100 - Inbuilt RO Purifier**
Storage Capacity	100 Litres
Storage Tank - Normal Water	100 Litres
No. of Faucets	3 or 4 or 7
Nett Weight in kg (Approx)	78
Water Purification Technology	RO
Purification Capacity	50 Litres/Hr or 100 Litres/Hr
Inlet Water TDS Recommended	Borewell Water - 300 PPM to 1800 PPM (Max)
Purification Stages	Fine Sediment Filter Activated Carbon Filter RO Membrane Post Carbon Filter UV (Optional)
Input Water TDS Rejection	90%
Recovery	30-40%
Power Supply (AC 50Hz)	180 to 240 V AC / 50 Hz
Control Type	Float Switch / Float Valve
MOC - Housing	Stainless Steel 202 Grade - 0.8 mm Thick
MOC - Normal Storage Tank	Stainless Steel 304 Grade - 0.8 mm Thick
MOC - Frame Structure	MS Angle - 3 mm Thickness
MOC - Faucets	Brass Chromium Plated
MOC - Drip Tray	Stainless Steel 304 Grade - 0.8 mm Thick
MOC - Leg	Stainless Steel 304 Grade - 2 mm Thick
MOC - Rear Cover	Stainless Steel 202 Grade - 0.8 mm Thick
Dimension - H100LSROUV50/100	L 600 mm × B 700 mm × H 1500 mm