TECHNICAL SPECIFICATIONS

MODEL H100LSUV Water Dispenser with Inbuilt RO/UV Purifier System

Storage Capacity - 100 Litres with Inbuilt UV

100 Litres / Hr Purifier System

Model	**H100LSUV - Inbuilt UV Purifier**
Dispenser Flow Rate	250 Litres / Hr
Storage Tank - Normal Water	100 Litres
No. of Faucets	3 or 4 or 7
Nett Weight in kg (Approx)	75
Water Purification Technology	UV
Inlet Water TDS Recommended	Good Water - Less than 300 PPM
Purification Stages	Fine Sediment Filter Activated Carbon Filter High Intensity UV Lamp
Input Water TDS Rejection	NA
Recovery	100%
Power Supply (AC 50Hz)	180 to 240 V AC / 50 Hz
Control Type	Float Switch / Float Valve
MOC - Housing	Stainless Steel 202 Grade - 0.8 mm Thick
MOC - Normal Storage Tank	Stainless Steel 304 Grade - 0.8 mm Thick
MOC - Frame Structure	MS Angle - 3 mm Thickness
MOC - Faucets	Brass Chromium Plated
MOC - Drip Tray	Stainless Steel 304 Grade - 0.8 mm Thick
MOC - Leg	Stainless Steel 304 Grade - 2 mm Thick
MOC - Rear Cover	Stainless Steel 202 Grade - 0.8 mm Thick
Dimension - H100LSUV	L 600 mm × B 700 mm × H 1500 mm