TECHNICAL SPECIFICATIONS

# MODEL H105LSNHC (Normal Hot & Cold) Touchless Sensor Based Water Dispenser

Hands-free dispensing | Normal, hot and cold water

| | |
|---|---|
| **Model** | **H105LSNHC-Touchless** |
| **Dispenser Flow Rate** | 150 Litres / Hr |
| **Storage Tank - Cold Water** | 50 Litres |
| **Storage Tank - Hot Water** | 5 Litres |
| **Storage Tank - Normal Water** | 50 Litres |
| **No. of Faucets** | 3 |
| **Faucet Type** | IR-Sensor-Touchless |
| **Heater Power in Watts** | 1000 |
| **Cooler Power in Watts** | 500 |
| **Net Weight in kg (Approx)** | 88 |
| **Power Supply (AC 50 Hz)** | 180 to 240 V AC 50 Hz |
| **Control Type** | Bubbler Operated Float Valve |
| **MOC - Housing** | Stainless Steel 202 Grade - 0.8 mm Thick |
| **MOC - Cold Storage Tank** | Stainless Steel 304 Grade - 0.8 mm Thick |
| **MOC - Hot Storage Tank** | Stainless Steel 304 Grade - 0.8 mm Thick |
| **MOC - Normal Storage Tank** | Stainless Steel 304 Grade - 0.8 mm Thick |
| **MOC - Faucets** | Brass Chromium Plated |

TECHNICAL SPECIFICATIONS

# MODEL H105LSNHC (Normal Hot & Cold) Touchless Sensor Based Water Dispenser

Hands-free dispensing | Normal, hot and cold water

| | |
|---|---|
| **MOC - Heater Coil** | Stainless Steel |
| **MOC - Drip Tray** | Stainless Steel 304 Grade - 0.8 mm Thick |
| **MOC - Leg** | Stainless Steel 304 Grade - 2 mm Thick |
| **MOC - Rear Cover** | Stainless Steel 202 Grade - 0.8 mm Thick |
| **MOC - Frame Structure** | MS Angle - 3 mm Thickness |
| **Heater Temperature Range** | 40 to 80°C (Thermostat Adjustable) |
| **Heater Protection** | Provided |
| **Heating Technology** | Double Thermostat Technology |
| **Probe / Steam Vent** | Provided |
| **Cooling Temperature Range** | 16 to 22°C (Thermostat Adjustable) |
| **Condenser Tubing** | Grooved Copper |
| **Insulation of Cooling Tank** | Polyurethane Foam - 50 mm Thick |
| **Compressor Make** | Emerson / Tecumseh |
| **Compressor Refrigerant** | R-134a |
| **Dimensions - H105LSNHC** | L: 530 mm x B: 560 mm x H: 1500 mm |