TECHNICAL SPECIFICATIONS

H110LSNHC Normal, Hot & Cold Bubbletop Water Dispenser

Model H110LSNHC • Bubbletop dispenser • Hot, cold and normal water

GENERAL & MATERIAL SPECIFICATIONS

Model	H110LSNHC-Bubbletop
Dispenser Flow Rate	200 Litres / Hr
Storage Tank – Cold Water	50 Litres
Storage Tank – Hot Water	5 Litres
Storage Tank – Normal Water	50 Litres
No. of Faucets	3
Heater Power	1500 W
Cooler Power	500 W
Net Weight (Approx.)	86 kg
Power Supply (AC 50Hz)	180 to 240 V AC / 50 Hz
Control Type	Bubbletop Can
MOC – Housing	Stainless Steel 202 Grade – 0.8 mm Thick
MOC – Cold Storage Tank	Stainless Steel 304 Grade – 0.8 mm Thick
MOC – Hot Storage Tank	Stainless Steel 304 Grade – 0.8 mm Thick
MOC – Normal Storage Tank	Stainless Steel 304 Grade – 0.8 mm Thick
MOC – Faucets	Brass Chromium Plated
MOC – Heater Coil	Stainless Steel
MOC – Drip Tray	Stainless Steel 304 Grade – 0.8 mm Thick
MOC – Leg	Stainless Steel 304 Grade – 2 mm Thick
MOC – Rear Cover	Stainless Steel 202 Grade – 0.8 mm Thick

TECHNICAL SPECIFICATIONS

H110LSNHC Normal, Hot & Cold Bubbletop Water Dispenser

Model H110LSNHC • Bubbletop dispenser • Hot, cold and normal water

PERFORMANCE, COMPONENTS & DIMENSIONS

MOC – Frame Structure	MS Angle – 3 mm Thickness
Heater Temperature Range	40 to 80°C (Thermostat Adjustable)
Heater Protection	Provided
Heating Technology	Double Thermostat Technology
Proper Steam Vent	Provided
Cooling Temperature Range	16 to 22°C (Thermostat Adjustable)
Condenser Tubing	Grooved Copper
Insulation of Cooling Tank	Polyurethane Foam – 50 mm Thick
Compressor Make	Emerson / Tecumseh
Compressor Refrigerant	R-134a
Dimension – H110LSNHC-Bubbletop	L 650 mm × B 560 mm × H 1500 mm