TECHNICAL SPECIFICATIONS

MODEL H150LSROUV50/100 (Normal Water Dispenser) with Inbuilt RO 100 Litres/Hr Purification System

Storage Capacity - 150 L

Model	**H150LSROUV50/100 - Inbuilt RO 100 LPH Purifier**
Storage Capacity	150 Litres
Storage Tank - Purified Water	150 Litres
No. of Faucets	3 or 4 or 7
Nett Weight in kg (Approx)	94
Water Purification Technology	RO
Purification Capacity	100 Litres/Hr
Inlet Water TDS Recommended	Borewell Water - 300 PPM to 2000 PPM (Max)
Purification Stages	Fine Sediment Filter Activated Carbon Filter RO Membrane Post Carbon Filter UV (Optional)
Input Water TDS Rejection	90%
Recovery	30-40%
Power Supply (AC 50Hz)	180 to 240 V AC / 50 Hz
Control Type	Float Switch
MOC - Housing	Stainless Steel 202 Grade - 0.8 mm Thick
MOC - Normal Storage Tank	Stainless Steel 304 Grade - 0.8 mm Thick
MOC - Faucets	Brass Chromium Plated
MOC - Drip Tray	Stainless Steel 304 Grade - 0.8 mm Thick
MOC - Leg	Stainless Steel 304 Grade - 2 mm Thick
MOC - Frame Structure	MS Angle - 3 mm Thickness
MOC - Rear Cover	Stainless Steel 202 Grade - 0.8 mm Thick
Dimension - H150LSROUV50/100	L 700 mm × B 1000 mm × H 1500 mm