H31LSNHCUV

Technical Specifications

Normal, Hot & Cold Water Cooler/Dispenser with Inbuilt UV Purifier

Model	H31LSNHCUV - Inbuilt UV Purifier
Dispenser Flow Rate	80 Litres/Hr
Storage Tank - Cold Water	16 Litres
Storage Tank - Hot Water	5 Litres
Storage Tank - Normal Water	16 Litres
No. of Faucets	3
Heater Power in Watts	1000
Cooler Power in Watts	350
Nett Weight in kg (Approx)	57
Water Purification Technology	UV
Inlet Water TDS Recommended	Good Water - Less than 300 PPM
Purification Stages	Fine Sediment Filter Activated Carbon Filter High Intensity UV Lamp
Input Water TDS Rejection	Nil
Recovery	100%
Power Supply (AC 50Hz)	180 to 240 V AC / 50 Hz
Control Type	Float Switch / Float Valve

H31LSNHCUV

Technical Specifications - Continued

MOC - Housing	Stainless Steel 202 Grade - 0.8 mm thick
MOC - Cold Storage Tank	Stainless Steel 304 Grade - 0.8 mm thick
MOC - Hot Storage Tank	Stainless Steel 304 Grade - 0.8 mm thick
MOC - Normal Storage Tank	Stainless Steel 304 Grade - 0.8 mm thick
MOC - Faucets	Brass Chromium plated
MOC - Heater Coil	Stainless Steel
MOC - Drip Tray	Stainless Steel 304 Grade - 0.8 mm thick
MOC - Leg	Stainless Steel 304 Grade - 2 mm thick
MOC - Rear Cover	Stainless Steel 202 Grade - 0.8 mm thick
Heater Temperature Range	40 to 80°C (Thermostat Adjustable)
Cooling Temperature Range	16 to 22°C (Thermostat Adjustable)
Condenser Tubing	Grooved Copper
Insulation of Cooling Tank	Polyurethane Foam - 50 mm thick
Compressor Make	Emerson / Tecumseh
Compressor Refrigerant	R-134a
Dimensions	L - 370 mm, B - 430 mm, H - 1350 mm