TECHNICAL SPECIFICATIONS

H31LSNHC Normal, Hot & Cold Bubbletop Water Dispenser

Model H31LSNHC • Bubbletop dispenser • Hot, cold and normal water

Model	H31LSNHC-Bubbletop
Dispenser Flow Rate	80 Litres / Hr
Storage Tank – Cold Water	14 Litres
Storage Tank – Hot Water	5 Litres
Storage Tank – Normal Water	14 Litres
No. of Faucets	3
Heater Power	1000 W
Cooler Power	350 W
Net Weight (Approx.)	57 kg
Power Supply (AC 50Hz)	180 to 240 V AC / 50 Hz
Control Type	Bubbletop Can
MOC – Housing	Stainless Steel 202 Grade – 0.8 mm Thick
MOC – Cold Storage Tank	Stainless Steel 304 Grade – 0.8 mm Thick
MOC – Hot Storage Tank	Stainless Steel 304 Grade – 0.8 mm Thick
MOC – Normal Storage Tank	Stainless Steel 304 Grade – 0.8 mm Thick
MOC – Faucets	Brass Chromium Plated
MOC – Heater Coil	Stainless Steel
MOC – Drip Tray	Stainless Steel 304 Grade – 0.8 mm Thick
MOC – Leg	Stainless Steel 304 Grade – 2 mm Thick
MOC – Rear Cover	Stainless Steel 202 Grade – 0.8 mm Thick
Heater Temperature Range	40 to 80°C (Thermostat Adjustable)
Cooling Temperature Range	16 to 22°C (Thermostat Adjustable)
Condenser Tubing	Grooved Copper
Insulation of Cooling Tank	Polyurethane Foam – 50 mm Thick
Compressor Make	Tecumseh
Compressor Refrigerant	R-134a
Dimension – H31LSNHC	L 570 mm × B 450 mm × H 1350 mm