TECHNICAL SPECIFICATIONS

MODEL H35LSNH - HOT Water Dispenser

Storage Capacity - 35 L (25 L NORMAL + 10 L HOT)

Model	**H35LSNH**
Storage Capacity	35 L (25 L NORMAL + 10 L HOT)
Storage Tank - Hot Water	10 Litres
Storage Tank - Normal Water	25 Litres
No. of Faucets	2
Heater Power in Watts	1000
Nett Weight in kg (Approx)	45
Power Supply (AC 50Hz)	180 to 240 V AC / 50 Hz
Control Type	Float Switch / Float Valve
MOC - Housing	Stainless Steel 202 Grade - 0.8 mm thick
MOC - Hot Storage Tank	Stainless Steel 304 Grade - 0.8 mm thick
MOC - Normal Storage Tank	SS304 Grade - 0.8 mm thick
MOC - Faucets	Brass Chromium plated
MOC - Heater Coil	Stainless Steel
MOC - Drip Tray	Stainless Steel 304 Grade - 0.8 mm thick
MOC - Leg	Stainless Steel 304 Grade - 2 mm thick
MOC - Rear Cover	Stainless Steel 202 Grade - 0.8 mm thick
Heater Temperature Range	40 to 80°C (Thermostat Adjustable)
Proper Steam Vent	Provided
Heater Protection	Double thermostat technology
Dimension - H35LSNH	L - 430 mm, B - 370 mm, H - 1350 mm