TECHNICAL SPECIFICATIONS

MODEL H45LSNHC (Normal Hot & Cold) Touchless Sensor Based Water Dispenser

Hands-free dispensing | Normal, hot and cold water

Model	**H45LSNHC-Touchless**
Dispenser Flow Rate	110 Litres / Hr
Storage Tank - Cold Water	20 Litres
Storage Tank - Hot Water	5 Litres
Storage Tank - Normal Water	20 Litres
No. of Faucets	3
Faucet Type	IR Sensor
Heater Power in Watts	1000
Cooler Power in Watts	350
Net Weight in kg (Approx)	57
Power Supply (AC 50 Hz)	180 to 240 V AC 50 Hz
Control Type	Float Switch
MOC - Housing	Stainless Steel 202 Grade - 0.8 mm Thick
MOC - Cold Storage Tank	Stainless Steel 304 Grade - 0.8 mm Thick
MOC - Hot Storage Tank	Stainless Steel 304 Grade - 0.8 mm Thick
MOC - Normal Storage Tank	Stainless Steel 304 Grade - 0.8 mm Thick
MOC - Faucets	Brass Chromium Plated

TECHNICAL SPECIFICATIONS

MODEL H45LSNHC (Normal Hot & Cold) Touchless Sensor Based Water Dispenser

Hands-free dispensing | Normal, hot and cold water

MOC - Heater Coil	Stainless Steel
MOC - Drip Tray	Stainless Steel 304 Grade - 0.8 mm Thick
MOC - Leg	Stainless Steel 304 Grade - 2 mm Thick
Frame Structure	MS Angle - 3 mm Thickness
MOC - Rear Cover	Stainless Steel 202 Grade - 0.8 mm Thick
Heater Temperature Range	40 to 80°C (Thermostat Adjustable)
Heater Protection	Provided
Heater Technology	Double Thermostat Technology
Cooling Temperature Range	16 to 22°C (Thermostat Adjustable)
Condenser Tubing	Grooved Copper
Insulation of Cooling Tank	Polyurethane Foam - 50 mm Thick
Compressor Make	Emerson / Tecumseh
Compressor Refrigerant	R-134a
Dimensions - H45LSNHC	L: 455 mm x B: 500 mm x H: 1350 mm