TECHNICAL SPECIFICATIONS

MODEL H50LSRO25 (Normal or Warm Water Dispenser) with Inbuilt RO + UV Purifier System

Storage Capacity - 50 L

Model	**H50LSRO25 - Inbuilt RO Purifier**
Storage Capacity	50 Litres
Storage Tank - Normal Water	50 Litres
No. of Faucets	2
Nett Weight in kg (Approx)	48
Water Purification Technology	RO
Purification Capacity	25 Litres / Hr
Inlet Water TDS Recommended	Borewell Water - 300 PPM to 1800 PPM (Max)
Purification Stages	Fine Sediment Filter Activated Carbon Filter RO Membrane Post Carbon Filter UV (Optional)
Input Water TDS Rejection	90%
Recovery	30-40%
Power Supply (AC 50Hz)	180 to 240 V AC / 50 Hz
Control Type	Float Switch / Float Valve
MOC - Housing	Stainless Steel 202 Grade - 0.8 mm Thick
MOC - Normal Storage Tank	SS304 Grade - 0.8 mm Thick
MOC - Faucets	Brass Chromium Plated
MOC - Drip Tray	Stainless Steel 304 Grade - 0.8 mm Thick
MOC - Leg	Stainless Steel 304 Grade - 2 mm Thick
MOC - Rear Cover	Stainless Steel 202 Grade - 0.8 mm Thick
Dimension - H50LSRO25	L 455 mm × B 500 mm × H 1350 mm