TECHNICAL SPECIFICATIONS

MODEL H50LSUV (Normal or Warm Water Dispenser) with Inbuilt RO or UV Purifier System

Model H50LSUV with 50 litre storage capacity and inbuilt UV purification, designed for reliable normal or warm water dispensing in commercial, industrial and institutional applications.

Model	**H50LSUV - Inbuilt UV Purifier**
Storage Capacity	50 Litres
Storage Tank - Normal Water	50 Litres
No. of Faucets	1 or 2
Net Weight	Approx. 43 kg
Water Purification Technology	UV
Purification Capacity	50 Litres / Hr
Inlet Water TDS Recommended	Good Water - Less than 300 PPM
Purification Stages	Fine Sediment Filter Activated Carbon Filter High Intensity UV Lamp
Input Water TDS Rejection	Nil
Recovery	100%
Power Supply (AC 50Hz)	180 to 240 V AC / 50 Hz
Control Type	Float Switch / Float Valve
MOC - Housing	Stainless Steel 202 Grade - 0.8 mm Thick
MOC - Normal Storage Tank	Stainless Steel 304 Grade - 0.8 mm Thick
MOC - Faucets	Brass Chromium Plated
MOC - Drip Tray	Stainless Steel 304 Grade - 0.8 mm Thick
MOC - Leg	Stainless Steel 304 Grade - 2 mm Thick
MOC - Rear Cover	Stainless Steel 202 Grade - 0.8 mm Thick
Dimension - H50LSUV	L 455 mm × B 500 mm × H 1350 mm