TECHNICAL SPECIFICATIONS

# MODEL H55LSNH - HOT Water Dispenser

**Storage Capacity - 55 L (50 L NORMAL + 5 L HOT)**

| | |
|---|---|
| **Model** | **H55LSNH** |
| **Storage Capacity** | 55 L (50 L NORMAL + 5 L HOT) |
| **Storage Tank - Hot Water** | 5 Litres |
| **Storage Tank - Normal Water** | 50 Litres |
| **No. of Faucets** | 2 |
| **Heater Power in Watts** | 1000 |
| **Nett Weight in kg (Approx)** | 45 |
| **Power Supply (AC 50Hz)** | 180 to 240 V AC / 50 Hz |
| **Control Type** | Float Switch / Float Valve |
| **MOC - Housing** | Stainless Steel 202 Grade - 0.8 mm thick |
| **MOC - Hot Storage Tank** | Stainless Steel 304 Grade - 0.8 mm thick |
| **MOC - Normal Storage Tank** | SS304 Grade - 0.8 mm thick |
| **MOC - Faucets** | Brass Chromium plated |
| **MOC - Heater Coil** | Stainless Steel |
| **MOC - Drip Tray** | Stainless Steel 304 Grade - 0.8 mm thick |
| **MOC - Leg** | Stainless Steel 304 Grade - 2 mm thick |
| **MOC - Rear Cover** | Stainless Steel 202 Grade - 0.8 mm thick |
| **Heater Temperature Range** | 40 to 80°C (Thermostat Adjustable) |
| **Proper Steam Vent** | Provided |
| **Heater Protection** | Double thermostat technology |
| **Dimension - H55LSNH** | L - 450 mm, B - 500 mm, H - 1350 mm |