TECHNICAL SPECIFICATIONS

MODEL H80LSRO50 Normal OR Warm Water Dispenser with Inbuilt RO + UV Purifier System

Storage Capacity - 80 L

Model	**H80LSRO50 - Inbuilt RO Purifier**
Storage Capacity	80 Litres
Storage Tank - Normal Water	80 Litres
No. of Faucets	2 or 3 or 4
Nett Weight in kg (Approx)	68
Water Purification Technology	RO
Purification Capacity	25 / 50 Litres / Hr
Inlet Water TDS Recommended	Borewell Water - 300 PPM to 1800 PPM (Max)
Purification Stages	Fine Sediment Filter Activated Carbon Filter RO Membrane Post Carbon Filter UV (Optional)
Input Water TDS Rejection	90%
Recovery	30-40%
Power Supply (AC 50Hz)	180 to 240 V AC / 50 Hz
Control Type	Float Switch / Float Valve
MOC - Housing	Stainless Steel 202 Grade - 0.8 mm Thick
MOC - Frame Structure	MS Angle - 3 mm Thickness
MOC - Normal Storage Tank	Stainless Steel 304 Grade - 2 mm Thick
MOC - Faucets	Brass Chromium Plated
MOC - Drip Tray	Stainless Steel 304 Grade - 0.8 mm Thick
MOC - Leg	Stainless Steel 304 Grade - 2 mm Thick
MOC - Rear Cover	Stainless Steel 202 Grade - 0.8 mm Thick
Dimension - H80LSRO50	L 530 mm × B 550 mm × H 1500 mm