TECHNICAL SPECIFICATIONS

MODEL H80LSUV (Normal or Warm Water Dispenser) with Inbuilt UV Purifier System

Model H80LSUV with 80 litre storage capacity and inbuilt UV purification, designed for reliable normal or warm water dispensing in commercial, industrial and institutional applications.

Model	**H80LSUV - Inbuilt UV Purifier**
Dispenser Flow Rate	150 Litres / Hr
Storage Tank - Normal Water	80 Litres
No. of Faucets	3 Taps
Net Weight	Approx. 63 kg
Water Purification Technology	UV
Inlet Water TDS Recommended	Good Water - Less than 300 PPM
Purification Stages	Fine Sediment Filter Activated Carbon Filter High Intensity UV Lamp
Input Water TDS Rejection	NA
Recovery	100%
Power Supply (AC 50Hz)	180 to 240 V AC / 50 Hz
Control Type	Float Switch / Float Valve
MOC - Housing	Stainless Steel 202 Grade - 0.8 mm Thick
MOC - Frame	MS Angle - 3 mm Thickness
MOC - Normal Storage Tank	Stainless Steel 304 Grade - 2 mm Thick
MOC - Faucets	Brass Chromium Plated
MOC - Drip Tray	Stainless Steel 304 Grade - 0.8 mm Thick
MOC - Leg	Stainless Steel 304 Grade - 2 mm Thick
MOC - Rear Cover	Stainless Steel 202 Grade - 0.8 mm Thick
Dimension - H80LSUV	L 530 mm × B 560 mm × H 1500 mm