TECHNICAL SPECIFICATIONS

MODEL H85LSNHC (Normal Hot & Cold) Touchless Sensor Based Water Dispenser

Hands-free dispensing | Normal, hot and cold water

Model	**H85LSNHC-Touchless**
Dispenser Flow Rate	150 Litres / Hr
Storage Tank - Cold Water	40 Litres
Storage Tank - Hot Water	5 Litres
Storage Tank - Normal Water	40 Litres
No. of Faucets	3
Faucet Type	IR-Sensor-Touchless
Heater Power in Watts	1000
Cooler Power in Watts	500
Net Weight in kg (Approx)	84
Power Supply (AC 50 Hz)	180 to 240 V AC 50 Hz
Control Type	Bubbler Operated Float Valve
MOC - Housing	Stainless Steel 202 Grade - 0.8 mm Thick
MOC - Cold Storage Tank	Stainless Steel 304 Grade - 0.8 mm Thick
MOC - Hot Storage Tank	Stainless Steel 304 Grade - 0.8 mm Thick
MOC - Normal Storage Tank	Stainless Steel 304 Grade - 0.8 mm Thick
MOC - Faucets	Brass Chromium Plated

TECHNICAL SPECIFICATIONS

MODEL H85LSNHC (Normal Hot & Cold) Touchless Sensor Based Water Dispenser

Hands-free dispensing | Normal, hot and cold water

MOC - Heater Coil	Stainless Steel
MOC - Drip Tray	Stainless Steel 304 Grade - 0.8 mm Thick
MOC - Leg	Stainless Steel 304 Grade - 2 mm Thick
MOC - Rear Cover	Stainless Steel 202 Grade - 0.8 mm Thick
MOC - Frame Structure	MS Angle - 3 mm Thickness
Heater Temperature Range	40 to 80°C (Thermostat Adjustable)
Heater Protection	Provided
Heating Technology	Double Thermostat Technology
Probe / Steam Vent	Provided
Cooling Temperature Range	16 to 22°C (Thermostat Adjustable)
Condenser Tubing	Grooved Copper
Insulation of Cooling Tank	Polyurethane Foam - 50 mm Thick
Compressor Make	Emerson / Tecumseh
Compressor Refrigerant	R-134a
Dimensions - H85LSNHC	L: 530 mm x B: 560 mm x H: 1500 mm