TECHNICAL SPECIFICATIONS

MODEL J500NHC (Normal Hot & Cold) Water Cooler / Dispenser System

Heavy Duty Industrial Water Cooler / Dispenser System

Model	**J500NHC**
Dispenser Flow Rate	500 Liters / Hr
Storage Tank - Cold Water	100 Liters
Cooling Capacity	100 Liters / Hr
Storage Tank - Normal Water	50 Liters
Storage Tank - Hot Water	10 Liters
No. of Faucets	4
Net Weight in kg (Approx)	110
Cooler Power in Watts	1450
Hot Power in Watts	1500
Power Supply (AC 50 Hz)	180 to 240 VAC / 50 Hz
Control Type	Float Valve - Automatic Flow Cut Off
MOC - Housing	Stainless Steel SS202 - 0.8 mm Thick
MOC - Cold Storage Tank	Stainless Steel SS304 - 0.8 mm Thick
MOC - Normal Storage Tank	Stainless Steel SS304 - 0.8 mm Thick

TECHNICAL SPECIFICATIONS

MODEL J500NHC (Normal Hot & Cold) Water Cooler / Dispenser System

Heavy Duty Industrial Water Cooler / Dispenser System

MOC - Hot Storage Tank	Stainless Steel SS304 - 0.8 mm Thick
MOC - Faucets	Brass Chromium Plated
MOC - Drip Tray	Stainless Steel SS304 - 0.8 mm Thick
MOC - Frame	Coated Steel - 3 mm Thick
MOC - Rear Cover	Stainless Steel SS202 - 0.8 mm Thick
Cooling Temperature Range	16 to 22°C (Thermostat Adjustable)
Heater Temperature Range	45 to 80°C (Thermostat Adjustable)
Heater Protection	Double Thermostat Technology
Low Water Level Protection	Provided
Proper Steam Vent	Provided
Condenser Tubing	Grooved Copper
Insulation of Cooling Tank	Polyurethane Foam - 50 mm Thick
Compressor Make	Emerson
Compressor Refrigerant	R134a - Eco Friendly
Dimension - J500NHC	Front: 900 mm, Side: 630 mm, H: 1500 mm